

Winnebago County Dust Control Policy

IT SHALL BE THE POLICY of Winnebago County to permit the application of dust palliative agents for the control of dust on granular surface county roads pursuant to the provisions of Chapter 318.8 of the Code of Iowa.

PERMIT REQUIRED

A person shall not apply to the road surface any materials without obtaining a permit from the County Engineer. Work performed under the permit shall be performed in conformity with the specifications herein provided. Signed permit applications shall be collected from the applicant by an approved contractor and submitted to the County Engineer. Permits expire October 1st each year.

PERMIT FEES

All fees shall be collected by the contractor and submitted to the County in a lump sum with the completed permits. Permit fees shall be as follows:

Before May 15 th	\$25.00
After May 15 th	\$50.00

PRE-APPROVED CONTRACTORS REQUIRED

A contractor shall not perform work under a permit without approval by the County Engineer. Approval may be granted if the contractor:

1. Is generally in good standing with the County.
2. Has submitted proof of insurance not less than \$1,000,000

Approved Contractors:

1. Deano's Dust Control - Mason City, IA
2. Woody's Dust Control - Rudd, IA
3. Freeborn County Coop Oil & Albert Lea, MN

PRE-APPROVED PRODUCTS AND SCHEDULE

Dust control products shall be approved prior to application. Approved products include:

1. Lignin Sulfonate
2. Magnesium Chloride
3. Calcium Chloride

Product selection and application rate shall be subject to owner-contractor agreement. Dust control products may be applied between May 15th and September 30th.

NOTIFICATION AND MARKING REQUIRED

The contractor shall notify the County three (3) business days prior to each application. The contractor shall mark the extents of treated areas with highly visible markers provided by the County Engineer immediately after each application. Markers are orange and indicate first application with 1 stripe and flip vertically to indicate second application with 2 stripes. Markers should be placed at the edge of the shoulder. Markers will be removed by the County after September each year.

MAINTENANCE OF TREATED AREAS

The County will prepare the road surface before each application and re-blade following applications as necessary to keep the road surface in a safe and proper condition.